


3M™ TWIN AXIAL PCI EXPRESS X8 EXTENDER ASSEMBLIES GEN 4.0,
8KH9 SERIES

BILL OF MATERIALS			
	ITEM	DESCRIPTION	QTY
1.0	PBA	PCB ASSY, PADDLECARD, PCIE X8	1
1.1	PCB	PCIE X8 (98 POS) SURFACEMOUNT 3M P/N: 78-9102-8020-1	1
1.2	CONN	CONNECTOR, PCIE (98 POS) SMT. X8 GEN 5	1
2.0	PCB	PCIE X8 EXTENDER (98 POS) CARD-EDGE 3M P/N: 78-9102-8014-4	1
3.0	CABLE	RIBBON TWINAX CABLE 3M P/N: SL8802/22-15FN5-00	AS REQUIRED
4.0	CABLE	RIBBON CABLE, 20 POSITION 3M P/N: HF447-20	AS REQUIRED
5.0	STRAIN RELIEF	ADHESIVE	AS REQUIRED
6.0	LABEL	SEE ASSEMBLY PART DETAIL	1

ORDERING INFORMATION
8KH9-0968-XXXX


- STANDARD LENGTHS DIM. "A"
0250 = [250 MM]
0500 = [500 MM]

NOTE :
NON-STANDARD LENGTHS AVAILABLE UPON REQUEST.
MAY REQUIRE HIGHER MOQ'S AND LONGER LEAD TIMES.






3M ELECTRONICS MATERIALS SOLUTIONS DIVISION
INTERCONNECT SOLUTIONS
<http://www.3m.com/TwinAx>

3M IS A TRADEMARK OF 3M COMPANY.
FOR TECHNICAL, SALES OR ORDERING
INFORMATION CALL 800-225-5373



- | NOTES | |
|-------|---|
| 1. | DIMENSIONS ARE IN MILLIMETERS. |
| 2. | 3M TWIN AXIAL CABLE DESCRIPTION:
30 AWG, SILVER PLATED SIGNAL WIRE
IMPEDANCE: 85 ±5 OHM
OVERALL RIBBON WIDTH: 24.90 MM
OVERALL RIBBON THICKNESS: 0.75 MM |
| 3. | REGULATORY INFORMATION:
VISIT 3M.com/regs OR CONTACT
YOUR 3M REPRESENTATIVE TO FIND
THE ROHS COMPLIANCE STATUS OF
THE 3M PART YOU ARE INTERESTED
IN. |
| 6. | THIS CABLE CONSTRUCTION HAS
A THIN ALUMINUM LAYER AT EACH
EDGE. USER SHOULD EVALUATE
ITS USE IN THEIR APPLICATION
AND, IF NECESSARY, INSULATING
TAPE MAY BE APPLIED TO COVER
THE ALUMINUM LAYER, AS USER
DEEMS APPROPRIATE. |
| 7. | PRODUCT SPECIFICATION: PS-0390. |
| 8. | FLAMMABILITY RATING
-TWINAX/AUX RIBBONS: UL94 HB
HORIZONTAL FLAME
TEST FOR INTERNAL WIRING
-PCBS: UL94V-0 |
| 9. | PADDLECARD PLATING:
30μ" MIN. GOLD PLATING
50μ" MIN. NICKEL UNDERPLATING. |
| 10 | UNLESS OTHERWISE NOTED,
REFERENCES TO INDUSTRY
SPECIFICATIONS ARE INTENDED
TO INDICATE SUBSTANTIAL
COMPLIANCE TO THE MATERIAL
ELEMENTS OF THE SPECIFICATION.
SUCH REFERENCES SHOULD NOT BE
CONSTRUED AS A GUARANTEE OF
COMPLIANCE TO ALL REQUIREMENTS
IN A GIVEN SPECIFICATION. |
| 11 | CLOTH TAPE WRAPPED AROUND CABLE
RIBBONS AT BACK OF EACH CONNECTOR.
ALSO, UP TO TWO ADDITIONAL TAPE
PIECES WILL BE WRAPPED AROUND THE
TWO CABLE RIBBONS SPACED EQUIDISTANT
FROM THE CONNECTOR ENDS AND EACH
OTHER, DEPENDING ON ASS'Y LENGTH (L):
L <= 0.2M: NO ADDITIONAL TAPE
0.2M < L <= 0.6M: 1 TAPE WRAP
0.6M < L <= 1.0M: 2 TAPE WRAP |
| 12 | LENGTH TOLERANCE:
±5MM FOR LENGTHS LESS THAN 0.5M.
±8MM FOR LENGTHS 0.5 TO 1.0 METER. |
| 13 | (X) DENOTES ITEM FIND NUMBER IN
TABLE 1: BILL OF MATERIALS. |
| 14 | (C) DENOTES CRITICAL DIMENSION. |

DESIGN REFERENCE		NEXT		ASSEMBLY		REV		ECO		ISSUE DATE AND DESCRIPTION		DRFT		CHKD	
DESG CODES						DRFT CASTIGLIONE		DATE MAR 15, 2019		INFO		DATE			
						CHKD M LETTANG		DATE AUG 15, 2022		APPVL		DATE			
DIVISION				DIVISION CODE				© 3M COPYRIGHT 2022 This document and the information it contains are 3M property and should not be reproduced or further distributed without 3M permission, or used or disclosed other than for 3M authorized purposes. All rights reserved.							
DO NOT SCALE DRAWING				SCALE $\frac{2}{1}$				TOLERANCES EXCEPT AS NOTED				 3M Center St. Paul, MN 55144			
 THIRD ANGLE PROJECTION				 INCHES				TITLE 8KH9-0968-XXXX CABLE ASSY, X8 GEN 4.0 SMT EXTENDER, PCIE							
INTERPRET PER ASME Y14.5 - 2018				 MILLIMETERS				CAGE NUMBER							
MAX SURFACE ROUGHNESS $\sqrt{\text{ }}$				$\sqrt{\text{ }}$				SIZE D				DRAWING NO. 78-5100-2687-1			
MAX SURFACES $\sqrt{\text{ }}$				$\sqrt{\text{ }}$				MODEL				REV. A			
☒ MARKED ONLY				ANGLE				DET. SETS				☐ YES ☒ NO			
												SHT 1 OF 6			

3M™ TWIN AXIAL PCI EXPRESS X8 EXTENDER ASSEMBLIES GEN 4.0, 8KH9 SERIES

Edgecard pin #	Side B Description	Name	CEM pin #
B01	+12 volt power	+12v	B01
B02	+12 volt power	+12v	B02
B03	+12 volt power	+12v	B03
B04	Ground	GND	B04
B05	SMBus clock	SMCLK	B05
B06	SMBus data	SMDAT	B06
B07	Ground	GND	B07
B08	+3.3 volt power	+3.3v	B08
B09	+TRST#	JTAG1	B09
B10	3.3v auxiliary power	3.3Vaux	B10
B11	Link Reactivation	WAKE#	B11
Mechanical Key			
B12	Clock Request Signal	CLKREQ#	B12
B13	Ground	GND	B13
B14	Transmitter Lane 0, Differential pair	PETp(0)	B14
B15		PETn(0)	B15
B16	Ground	GND	B16
B17	Presence detect	PRSNT2#	B17
B18	Ground	GND	B18
B19	Transmitter Lane 1, Differential pair	PETp(1)	B19
B20		PETn(1)	B20
B21	Ground	GND	B21
B22	Ground	GND	B22
B23	Transmitter Lane 2, Differential pair	PETp(2)	B23
B24		PETn(2)	B24
B25	Ground	GND	B25
B26	Ground	GND	B26
B27	Transmitter Lane 3, Differential pair	PETp(3)	B27
B28		PETn(3)	B28
B29	Ground	GND	B29
B30	Emergency Pwr Reduct	PWRBRK#	B30
B31	Presence detect	PRSNT2#	B31
B32	Ground	GND	B32
B33	Transmitter Lane 4, Differential pair	PETp(4)	B33
B34		PETn(4)	B34
B35	Ground	GND	B35
B36	Ground	GND	B36
B37	Transmitter Lane 5, Differential pair	PETp(5)	B37
B38		PETn(5)	B38
B39	Ground	GND	B39
B40	Ground	GND	B40
B41	Transmitter Lane 6, Differential pair	PETp(6)	B41
B42		PETn(6)	B42
B43	Ground	GND	B43
B44	Ground	GND	B44
B45	Transmitter Lane 7, Differential pair	PETp(7)	B45
B46		PETn(7)	B46
B47	Ground	GND	B47
B48	Presence detect	PRSNT2#	B48
B49	Ground	GND	B49

Edgecard pin #	Side A Description	Name	CEM pin #
A01	Presence detect	PRSNT#1	A01
A02	+12 volt power	+12v	A02
A03	+12 volt power	+12v	A03
A04	Ground	GND	A04
A05	TCK	JTAG2	A05
A06	TDI	JTAG3	A06
A07	TDO	JTAG4	A07
A08	TMS	JTAG5	A08
A09	+3.3 volt power	+3.3v	A09
A10	+3.3 volt power	+3.3v	A10
A11	Fundamental reset	PERST#	A11
Mechanical Key			
A12	Ground	GND	A12
A13	Reference Clock, Differential pair	REFCLK+	A13
A14		REFCLK-	A14
A15	Ground	GND	A15
A16	Receiver Lane 0, Differential pair	PERp(0)	A16
A17		PERn(0)	A17
A18	Ground	GND	A18
A19	Manufacturer Test Mode	MFG	A19
A20	Ground	GND	A20
A21	Receiver Lane 1, Differential pair	PERp(1)	A21
A22		PERn(1)	A22
A23	Ground	GND	A23
A24	Ground	GND	A24
A25	Receiver Lane 2, Differential pair	PERp(2)	A25
A26		PERn(2)	A26
A27	Ground	GND	A27
A28	Ground	GND	A28
A29	Receiver Lane 3, Differential pair	PERp(3)	A29
A30		PERn(3)	A30
A31	Ground	GND	A31
A32	Reserved	RSVD	A32
A33	Reserved	RSVD	A33
A34	Ground	GND	A34
A35	Receiver Lane 4, Differential pair	PERp(4)	A35
A36		PERn(4)	A36
A37	Ground	GND	A37
A38	Ground	GND	A38
A39	Receiver Lane 5, Differential pair	PERp(5)	A39
A40		PERn(5)	A40
A41	Ground	GND	A41
A42	Ground	GND	A42
A43	Receiver Lane 6, Differential pair	PERp(6)	A43
A44		PERn(6)	A44
A45	Ground	GND	A45
A46	Ground	GND	A46
A47	Receiver Lane 7, Differential pair	PERp(7)	A47
A48		PERn(7)	A48
A49	Ground	GND	A49

ALL GROUNDS ARE TIED TOGETHER IN PCBS

Regulatory: For regulatory information about this product, visit 3M.com/regs or contact your 3M representative.

Technical Information: The technical information, recommendations and other statements contained in this document are based upon tests or experience that 3M believes are reliable, but the accuracy or completeness of such information is not guaranteed.

Product Use: Many factors beyond 3M's control and uniquely within user's control can affect the use and performance of a 3M product in a particular application. Given the variety of factors that can affect the use and performance of a 3M product, user is solely responsible for evaluating the 3M product and determining whether it is fit for a particular purpose and suitable for user's method of application.

Warranty, Limited Remedy, and Disclaimer: Unless an additional warranty is specifically stated on the applicable 3M product packaging or product literature, 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF DEALING, CUSTOM OR USAGE OR TRADE. If the 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

Limitation of Liability: Except where prohibited by law, 3M will not be liable for any loss or damage arising from the 3M product, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including warranty, contract, negligence or strict liability.

3M Company
Electronics Materials Solutions Division
13011 McCallen Pass, Bldg. C
Austin, TX 78753-5380
1-800-225-5373
www.3M.com/interconnect

DESIGN REFERENCE		NEXT ASSEMBLY		REV	ECO	ISSUE DATE AND DESCRIPTION		DRFT	CHKD
XREF CODES				DRP	CASTIGLIONE		DATE	DATE	
				CHKD	M LETTANG		DATE	DATE	
DIVISION		DIVISION CODE		3M		© 3M. COPYRIGHT 2022			
DO NOT SCALE DRAWING		SCALE 1/1		TOLERANCES EXCEPT AS NOTED		3M Center St. Paul, MN 55144			
THIRD ANGLE PROJECTION		INCHES		MILLIMETERS		This document and the information it contains are 3M property and may not be reproduced or further distributed without 3M permission, or used or disclosed other than for 3M authorized purposes. All rights reserved.			
MAX SURFACE ROUGHNESS		INTERPRET PER ASME Y14.5 - 2018		CAGE NUMBER		SIZE	DRAWING NO.	REV.	
✓ MARKED ONLY				D		78-5100-2687-1		A	
				MODEL		DET		SHT 2 OF 2	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

3M:

[8KH9-0968-0250](#) [8KH9-0968-0500](#)