

har-flex THR str f 9.05mm 16p PL1 220pcs

[Spotted an error?](#) |  [Print page](#)
[Back](#) >


Image is for illustration purposes only.
Please refer to product description.

- Identification
- Version
- Technical characteristics
- Material properties

Part number	15 22 016 2401 000
Description	har-flex THR str f 9.05mm 16p PL1 220pcs
Typblad	 PDF
Datablad	 PDF

[Login to MyHARTING](#)
for pricing and stock check

Quantity:
[Shopping cart](#) >

[Email inquiry](#) >

Need assistance?


Customer service

Your HARTING customer
service representative:

866-278-0306

customerservice-usa@harting.com

Catalogue

Selection Guide for Mezzanine
Applications - Page


[Browse](#)
 [Download](#)

Identification

Category	Connector
Series	har-flex®
Element	Female connector
Description of the contact	Straight
Termination method	THR connection

[Top](#)

Version

Connection type	PCB to PCB
Number of contacts	16
Performance level	1
Pack contents	220 pieces on reel

[Top](#)

Technical characteristics

Contact rows	2
Contact spacing (mating side)	1.27 mm
Stacking height	9.05 mm
Clearance distance	≥ 0.4 mm
Creepage distance	≥ 0.4 mm
Insulation resistance	> 10 ⁹ Ω
Contact resistance	< 25 mΩ
Limiting temperature	-55 ... +125 °C
Test voltage U _{r.m.s.}	0.5 kV
CTI	= 175
Flammability acc. to UL 94	V-0

[Top](#)

Material properties

Material (insert)	LCP
Material (contacts)	Copper alloy
Surface (contacts)	Tin plated Termination side Au over Pd/Ni Mating side
RoHS compliant	Yes

[Top](#)

Downloads

Title	Downloads
-------	-----------

Typblad	 PDF
---------	---

Datablad	 PDF
----------	---

Typblad	 CGM
---------	---

Typblad	 DXF
---------	---

Title	Downloads
CAD-data 3D	 STEG
CAD-data 3D	 JT

Recently viewed

There are no current visited product detail pages.

Recently searched

No searches have been done yet.



[Home](#) | [Contact](#) | [Privacy Policy](#) | [Terms of Use](#) | [Sales and delivery conditions](#) | [Imprint](#)

HARTING contact: HARTING Inc. of N.America | Bowes Road 1370 | 60123-5538 Elgin | USA
HARTING support: 866-278-0306 | [✉ E-mail address](#) (For questions regarding products, orders and user accounts)
Website support: +49 5772 47-9399 | [✉ E-mail address](#) (For technical problems regarding the website)

