




REVISIONS					
P	LTR	DESCRIPTION	DATE	DWN	APVD
	C	REVISED PER ECR-10-020319	13OCT2010	HMR	TM
	D	REVISED PER ECR-14-000206	26DEC2013	PV	RB




1717674-2
SCALE 2:1



1717674-3
SCALE 2:1




1717674-4
SCALE 2:1




SCALE 2:1

- ① MATERIAL: 15% GLASS FILLED THERMOPLASTIC
COLOR: BLACK
② MATERIAL: 15% GLASS FILLED THERMOPLASTIC
COLOR: (SEE TABLE)
③ MATERIAL: SILICONE
COLOR: GREEN



4. WIRE INSULATION RANGE: $\varnothing 2.24 \sim \varnothing 3.94$



A - A
OPEN POSITION



1717674-1 SHOWN



GREEN	1717674-4
YELLOW	1717674-3
GRAY	1717674-2
RED	1717674-1
TPA COLOR	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN Y. KATO 15JAN2004	TE Connectivity		
DIMENSIONS: mm		CHK S. MANABE 15JAN2004			
TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± 1 PLC ± 2 PLC ± 3 PLC ± 4 PLC ± ANGLES ± FINISH		APVD S. MANABE 15JAN2004	NAME CAP ASSY, 4 POS. BRACKET REVERSE TYPE AMP SEAL 16		
MATERIAL		PRODUCT SPEC 108-2184	SIZE A260779		
		APPLICATION SPEC 114-13065	CAGE CODE C-1717674		
		WEIGHT	DRAWING NO 1717674		
		CUSTOMER DRAWING	RESTRICTED TO		
			SCALE 3:1 SHEET 1 OF 1 REV D		

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1717674-2](#)