

VS-15-DSUB-20-LI-5,0 - D-SUB cable

1656288

<https://www.phoenixcontact.com/us/products/1656288>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Assembled D-SUB cable shielded, 15-pos., stranded (7-wire), cable color RAL 7000 (gray), IP20 degree of protection, head 1 with socket shell 2 and straight cable outlet, head 2 with pin shell 2 and straight cable outlet, length: 5 m

Commercial data

Item number	1656288
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	AB19
Product key	ABNCAS
Catalog page	Page 218 (C-2-2013)
GTIN	4046356029766
Weight per piece (including packing)	333.9 g
Weight per piece (excluding packing)	295.6 g
Customs tariff number	85444290
Country of origin	CN

VS-15-DSUB-20-LI-5,0 - D-SUB cable

1656288

<https://www.phoenixcontact.com/us/products/1656288>



Technical data

Product properties

Type	D-SUB
Product type	Data cable preassembled
Sensor type	Universal
Number of positions	15
Cable outlet	straight

Insulation characteristics

Overvoltage category	III
Degree of pollution	2

Electrical properties

Rated current	1 A
Operating voltage	30 V
Transmission medium	Copper

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 50
-----------------------------	------

Material specifications

Contact material	Copper alloy
Contact surface material	gold-plated
Housing material	PVC
Outer sheath, material	PVC

Connection data

Connection technology

Connection method	D-SUB
-------------------	-------

Conductor connection

Connection method	D-SUB
-------------------	-------

Connector

Connection 1

Type	Socket straight D-SUB 15
Number of positions	15

Connection 2

Type	Plug straight D-SUB 15
Number of positions	15

VS-15-DSUB-20-LI-5,0 - D-SUB cable

1656288

<https://www.phoenixcontact.com/us/products/1656288>



Cable/line

External cable diameter	28 mm
Outer sheath, material	PVC
External sheath, color	beige
Single wire, cross section	28 mm ²
Cable cross section	0.08 mm ²
AWG signal line	28
Shielding	Aluminum-coated foil, tinned copper braided shield

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
	IP20
Ambient temperature (operation)	0 °C ... 70 °C

VS-15-DSUB-20-LI-5,0 - D-SUB cable


1656288

<https://www.phoenixcontact.com/us/products/1656288>




Drawings

Circuit diagram



Dimensional drawing




VS-15-DSUB-20-LI-5,0 - D-SUB cable

1656288


<https://www.phoenixcontact.com/us/products/1656288>



Schematic diagram



Dimensional drawing




VS-15-DSUB-20-LI-5,0 - D-SUB cable

1656288

<https://www.phoenixcontact.com/us/products/1656288>



Schematic diagram



VS-15-DSUB-20-LI-5,0 - D-SUB cable

1656288

<https://www.phoenixcontact.com/us/products/1656288>



Approvals

🔗 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1656288>



EAC

Approval ID: 19060508

VS-15-DSUB-20-LI-5,0 - D-SUB cable

1656288

<https://www.phoenixcontact.com/us/products/1656288>



Classifications

ECLASS

ECLASS-12.0	27060390
ECLASS-11.0	27060390
ECLASS-13.0	27060307

ETIM

ETIM 9.0	EC000748
----------	----------

UNSPSC

UNSPSC 21.0	26121600
-------------	----------

VS-15-DSUB-20-LI-5,0 - D-SUB cable



1656288

<https://www.phoenixcontact.com/us/products/1656288>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com