

LOC	DIST	REVISIONS 変更					
		P	LTR	DESCRIPTION	DATE	DWN	APVD
J			A3	REVISED PER ECO-11-005140	05APR2011	RK	HMR






TABLE-1

POS. 極数	CAP ASSEMBLY P/N
8	1376350
	1473793




TABLE-2

	FINISH めっき	TERMINAL P/N 端子型番	APPLICABLE WIRE RANGE 適用電線
SIGNAL 025	TIN	1123343-1	AVSS/AVSSH-f/AESSX 0.3~0.5mm ²
	SELECTIVE GOLD	1123343-2	CAVS/CAVUS 0.22~0.5mm ²

PAPER BOX ダンボール	PLASTIC BAG ビニール袋	BLACK	1376352-2
PAPER BOX ダンボール	PLASTIC BAG ビニール袋	NATURAL	1376352-1
OUTER 外装	INNER 内装	COLOR	PART NUMBER
PACKING STYLE 梱包形態			

- 1.RETAINER SHOULD BE SET TO THE PRE-ASSEMBLY POSITION WITHIN THE PLUG HOUSING WHEN SHIPPED TO THE CUSTOMER.
- 2.THE RETENSION LATCH OF THE PLATE MUST BE OUT SIDE OF PLUG HOUSING WHEN PRE-ASSEMBLY.
- 3.RETAINER RETENSION FORCE FROM HOUSING;30N MIN.
- 4.INSTRUCTION SHEET NO.411-5928
- 5.PART NO. OF CAP HOUSING TO BE MATED ; SEE TABLE-1
- 6.APPLIED TERMINAL ; SEE TABLE-2

1. プラグハウジングにリテーナを仮止めして出荷される。
2. 仮係止時リテーナ突起がハウジングの外側に出ていること。
3. リテーナの仮係止保持力は30N MIN.
4. 取扱説明書NO. 411-5928
5. 嵌合相手ハウジング型番 ; TABLE-1参照
6. 適用端子 ; TABLE-2参照

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN N. YASUDA 05JUL00	TE Connectivity			
		CHK N. SAI 06JUL00				
		APVD N. SAI 06JUL00	NAME 025 SERIES I/O CONNECTOR 8POSITION PLUG HOUSING ASSEMBLY			
DIMENSIONS: 単位: mm		TOLERANCES UNLESS OTHERWISE SPECIFIED: 一般公差 = ± 0.3		SIZE A3		
		0-PLC ± 1-PLC ±0.5 2-PLC ±0.13 3-PLC ±0.013 4-PLC ±0.0001 ANGLES ±3°		CAGE CODE 00779		
		PRODUCT SPEC 108-5668		DRAWING NO C-1376352		
		APPLICATION SPEC 114-5250		RESTRICTED TO		
MATERIAL 材料 PBT		FINISH 仕上 NATURAL		SCALE 尺度 2:1		
		WEIGHT 1.6 g		SHEET 1 OF 1		
		CUSTOMER DRAWING		REV A3		

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[TE Connectivity:](#)

[1376352-1](#)