

AUTOMOTIVE SEALS & CAVITY PLUGS



✓ Active

TE CONNECTIVITY (TE)

070 TYPE RUBBER PLUG

Econoseal , Econoseal J - 070

2822352-1

TE Internal Number: 2822352-1

EU RoHS Compliant

EU ELV Compliant

Cable Insulation Diameter 1.4 – 2.4 mm [.059 – .094 in]

Seal Type Single Wire Seal (SWS)

Material NBR

Shore A Hardness 38

Lubricant Content Yes

 **PRODUCT DRAWING**
Japanese

 **3D PDF**

DOCUMENTATION

Product Drawings

070 TYPE RUBBER PLUG

PDF

Japanese

CAD Files

3D PDF

PDF

3D

Customer View Model

2D_DXF.ZIP

English

Customer View Model

3D_IGS.ZIP

English

Customer View Model

3D_STP.ZIP

English

Product Specifications

Product Specification

AMP-ECONOSEAL "J"-II Connector

PDF

Japanese

AMP-ECONOSEAL-J Mark II+ Connector

PDF

English

AMP-ECONOSEAL-J Mark II+ Connector

PDF

Japanese

AMP Econoseal -J Mark II= Sensor Connector

PDF

English

AMP Econoseal -J Mark II= Sensor Connector

PDF

Japanese

Qualification Test Report

ECONOSEAL J MK-II+ CONNECTOR

PDF

Japanese

Econoseal-J Mark II Connector

PDF

Japanese

Product Environmental Compliance

TE Material Declaration

MD_2822352-1_022620172132_dmtec

PDF

English

Agency Approvals

Agency Approval Document

Econoseal Mark II J Series Connector REPORT

PDF

English

FEATURES



Please review product documents or [contact us](#) for the latest agency approval information.

Please Note: Use the Product Drawing for all design activity.

Product Type Features

Seal Type Single Wire Seal (SWS)

Body Features

Material NBR

Color Black

Dimensions

Cable Insulation Diameter 1.4 – 2.4 mm [.059 – .094 in]

Usage Conditions

Operating Temperature Range -30 – 105 °C [-22 – 221 °F]

Industry Standards

UL Flammability Rating None

Packaging Features

Packaging Method Bag

Packaging Quantity 1000

Other

Shore A Hardness 38

Lubricant Content Yes

PRODUCT COMPLIANCE



Statement of Compliance

Statement of Compliance

PDF
