



Search by part # or keyword

Products

Industries & Solutions

Resources

TE Store

Sign In



Connectors > D-Shaped Connectors > D-Sub Connector Contacts

206793-1

SZ 20,SOCKET, NON-MAG



AMPLIMITE

TE Internal #: **206793-1**

TE Internal Description: **SZ 20,SOCKET, NON-MAG**

Mil-Spec: **G-10-S1**

Contact Type : **Socket**

Contact Style : **Long**

Contact Size : **20**

Contact Base Material : **Copper Alloy**

Contact Mating Area Plating Material : **Gold over Copper**

Order Samples

Compatible Parts & Tooling

Purchase items directly from TE.com

Free Shipping to select countries. Exclusions apply. See complete details at [TE Store FAQs](#)

QTY:

Extended Price:

We are here to help!

Get in touch with our product experts.



CHAT WITH US



EMAIL US



CALL US

Documents

Features

Product Compliance

Product Drawings

SZ 20,SOCKET, NON-MAG

SZ 20,SOCKET, NON-MAG English

CAD Files

3D PDF

3D_CVM_CVM_206793-1_U.pdf 3D

Customer View Model

ENG_CVM_CVM_206793-1_U.2d_dxf.zip

English

ENG_CVM_CVM_206793-1_U.3d_igs.zip English

ENG_CVM_CVM_206793-1_U.3d_stp.zip

English

Datasheets & Catalog Pages

Sealed AMPLIMITE D-Subminiature Connectors

ENG_DS_1-1773853-7_dsub67_0516.pdf

English

Product Specifications

Application Specification

ENG_SS_114-10014_F.pdf English

Product Environmental Compliance

REACH Substance Communication Document

ENG_PC_RSCD_Lead_1.pdf English

Please review product documents or [contact us](#) for the latest agency approval information. Please Note: Use the Product Drawing for all design activity.

Product Type Features Connector & Contact Terminates To : **Wire & Cable**

Contact Features Contact Type : **Socket**
Contact Style : **Long**
Contact Size : **20**
Contact Base Material : **Copper Alloy**
Contact Mating Area Plating Material : **Gold over Copper**
Contact Current Rating (Max) (A): **7.5**

Termination Features Termination Method to Wire & Cable : **Crimp**

Dimensions Post Diameter : **.069 mm [1.75 in]**
Wire Size (AWG): **24 – 20**
Wire Size (mm²): **.2 – .52**

Usage Conditions Operating Temperature Range : **-55 – 125 °C [-67 – 257 °F]**

Operation/Application Circuit Application : **Signal**



[ABOUT TE CONNECTIVITY](#)

[FOR PARTNERS](#)

[SUPPORT](#)

[CALL US](#)

[LIVE CHAT](#)

[UNITED STATES \(EN\)](#)