

353907-1 Product Details

 [Share](#)  [Print](#)  [Email](#)



353907-1

TE Internal Number: 353907-1
 Active

 [View 3D PDF](#)

1.5mm AMP Mini CT Connectors

 Always EU RoHS/ELV Compliant (Statement of Compliance)

Product Highlights:

- Wire-to-Board, Wire-to-Board / Wire-to-Wire / Wire-to-Panel, Wire-to-Panel, Wire-to-Wire
- Applies To Wire/Cable
- Contact
- Contact Type = Socket
- Wire/Cable Size = 24 - 28 AWG

[View all Features](#)

Quick Links

- ▶ [Check Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [View Housings \(38\)](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)

Documentation & Additional Information

Product Drawings:

- [AMP MINI COMMON TERMINATED \(CT\) CONNECTOR 1.5mm PIT...](#) (PDF, English)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- [AMP Mini Common Termination \(CT\) Connector 1.5mm Pit...](#) (PDF, English)
- [1.5MM PITCH SIGNAL MATE CONNECTOR](#) (PDF, Japanese)
- [AMP Mini CT Connector 1.5mm Pitch \(Crimp Type\), Lead...](#) (PDF, Japanese)

Application Specifications:

- [AMP MINI COMMON TERMINATION \(CT\) CONNECTOR, 1.5MM PI...](#) (PDF, English)

Instruction Sheets:

- [1.5mm Pitch Mini CT DC Drawer Connector SF Type](#) (PDF, Japanese)
- [1.5mm Pitch Mini CT Hybrid Drawer Connector SF Type](#) (PDF, Japanese)
- [1.5mm Pitch Mini CT Hybrid Drawer Connector Slim Type](#) (PDF, Japanese)

CAD Files: (CAD Format & Compression Information)

- [2D Drawing](#) (DXF, Version J)
- [3D Model](#) (IGES, Version J)
- [3D Model](#) (STEP, Version J)

Related Products:

- [Tooling](#)
- [Housings \(38\)](#)

[List all Documents](#)

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- [Product Type](#) = Contact
- Termination Method to Wire/Cable = Crimp
- UL File Number = E28476
- CSA File Number = LR 7189-133

Electrical Characteristics:

- Contact - Rated Current (A) = 2
- Operating Voltage Reference = AC/DC, AC, DC
- Operating Voltage (VAC) = 50
- Operating Voltage (VDC) = 50

Termination Features:

- Wire/Cable Size (AWG) = 24 - 28

Contact Features:

- Contact Type = Socket
- Contact Plating, Mating Area, Material = Pre-Tin
- Contact Plating, Mating Area, Thickness (µm [µin]) = 0.2 [7.87]

Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Not relevant for lead free process
- RoHS/ELV Compliance History = Always was RoHS compliant
- Agency/Standard = CSA, UL

Environmental:

- Operating Temperature (°C [°F]) = -30 - +105 [-22 - +221]

Conditions for Usage:

- Applies To = Wire/Cable
- Accepts Wire Insulation Diameter, Range (mm [in]) = 0.85 - 1.05 [0.0334 - 0.041]

Operation/Application:

- Application Use = Wire-to-Board, Wire-to-Board / Wire-to-Wire / Wire-to-Panel, Wire-to-Panel, Wire-to-Wire
- Contact Transmits (Typical Application) = Signal (Data)
- Pick and Place Cover = Without

Packaging Features:

- Packaging Method = Strip

Other:

- Brand = AMP

Corporate Information

[About TE](#)
[Investors](#)
[News Room](#)
[Supplier Portal](#)
[Careers](#)
[Terms & Conditions](#)
[Privacy Policy](#)

Quick Links

[Check Distributor Inventory](#)
[Cross Reference Products](#)
[Find Documents & Drawings](#)
[Product Compliance Support Center](#)
[Site Map](#)

Customer Support

[Email or Chat With Us](#)
[Find a Phone Number](#)
[Search Knowledge Base](#)
[Manage Your Account](#)

Keep Me Informed

Receive TE News, Events & Technology Updates

Enter your email address 

