

Samples Request

- Find by Feature
- Browse by Category
- Browse by Application
- Share

Search →

Enter part number or keyword

- Search Results (0)
- Search Options

No Search Results

Select a product type to narrow your search:

Connector ▾

Results with your selections: --

Family

- 0.64
- 040
- 070
- 56
- 59
- 090
- 187
- ACT
- ATS
- Apex
- BTS
- Bus-Bar
- CTS

Search → Clear

Cavities

- 1
- 2
- 3
- 4
- 5
- 6
- 7
- 8
- 9
- 10
- 11
- 12
- 13

Search → Clear

Gender

- Female
- Male

Search → Clear

Sealed

- Sealed
- Unsealed

Search → Clear

Terminal(s) blade size [mm]

Mixed - Results will have exactly your selections in the same connector.

- 0.50
- 0.64
- 0.8
- 1.0
- 1.2
- 1.5
- 1.8
- 2.0 (round)
- 2.3
- 2.4 (round)
- 2.5
- 2.6
- 2.8

Search → Clear

Product Segment

- Headers
- High Power
- Safety Restraint Systems (SRS)
- Standard Automotive

Search → Clear

Application

- A/C Compressor
- Actuator
- Aerial / Antenna
- Airbag
- Alternator
- Antenna - Keyless System
- CAN
- Camera
- Cigar Lighter / Power Outlet
- Diagnostic
- Door To Body
- Electrovalve - Cold Start
- Fan - Engine Cooling

Search → Clear

Clear Search →

4 Way Black Weather Pack Shroud Sealed Male Connector, Max Current 20 amps

Part #12020830

Question about this product?

- Attributes
- Documents (6)
- Related Products (15)

Part # :	12020830
Description :	4 Way Black Weather Pack Shroud Sealed Male Connector, Max Current 20 amps
Product Type :	Connector
Status :	✔ Active
Family :	Weather Pack
Cavities :	4
Terminal(s) blade size [mm] :	2.6
Sealed :	Sealed
Gender :	Male
Temperature range [°C] :	-40 to 125
Material :	PA66
Weight [g] :	10.7
Color :	Black
ELV compliant :	✔ Yes
RoHS compliant :	✔ Yes
Application :	Inline (Wire to Wire)

Certain products listed on this website may be subject to restricted usage or distribution or may not be available. For additional information, please contact your local sales office.